

24654

Lighting/Speaker stand »Pro«

Product variant

24654-000-55 - black

Data

Base dimensions	550 x 550 mm
EAN	4016842122721
Gewicht	17.4 kg
Height	from 1,420 to 2,420 mm
Height adjustment	spring-loaded bolt and locking screw
Leg construction	flat steel plate
Material	steel
Max. load capacity*	30 kg
Quality level	Starline
Rod combination	2-piece folding design
Special features	integrated shock absorber; gradual height adjustment system: depending on the requirements, there are three ways to position the distance rod
Tube end(s)	diameter 35 mm, integrated threaded bush M10 for crossbars
Type	black



Attractive stand for lights and loudspeaker cabinets. Thanks to the heavy, flat steel plate (550 x 550 mm), the stand is ideal for use where space is at a premium. Depending on requirements, there are three ways to position the pole. In addition to the centric and off-center position, the tube combination can also be mounted in the corner. A carrying handle, a cable management system and four stable feet are further useful features. The usable height is between 1,420 and 2,420 mm and can be reached in 5 steps of 200 mm. The tried and tested K&M clamping screw and the robust locking bolt are used for fixing. The integrated M10 threaded bush enables the attachment of a truss or the direct attachment of lights. The maximum centric load capacity with full extension is 30 kg.