

21351

Distance rod

Product variant

US-21351-000-55 - black

Data

Gewicht 4.85 II Height from 33.43 to 54.2 Height adjustment locking screw and safety hor Material ste Max. load capacity 77.162 II Rod combination 2-piece folding design Special features for precise and vertical Tube end(s) diameter 1.378", threaded bolt M3		
Height from 33.43 to 54.2 Height adjustment locking screw and safety how Material stem Max. load capacity 77.162 light Rod combination 2-piece folding design Special features for precise and vertical Tube end(s) diameter 1.378", threaded bolt Mixing Special features for precise and vertical diameter 1.378", threaded bolt Mixing Special features for precise and vertical diameter 1.378", threaded bolt Mixing Special features for precise and vertical features features for precise and vertical features feature	EAN	4016842122912
Height adjustment locking screw and safety how Material stem Max. load capacity 77.162 li Rod combination 2-piece folding design Special features for precise and vertical Tube end(s) diameter 1.378", threaded bolt Max.	Gewicht	4.85 lbs
Material ste Max. load capacity 77.162 II Rod combination 2-piece folding design Special features for precise and vertical Tube end(s) diameter 1.378", threaded bolt M3	Height	from 33.43 to 54.21"
Max. load capacity 77.162 Rod combination 2-piece folding design Special features for precise and vertical Tube end(s) diameter 1.378", threaded bolt Maximum Tube end(s) threaded bolt	Height adjustment	locking screw and safety hook
Rod combination 2-piece folding design Special features for precise and vertical Tube end(s) diameter 1.378", threaded bolt M2	Material	steel
Special features for precise and vertical Tube end(s) diameter 1.378", threaded bolt M2	Max. load capacity	77.162 lbs
Tube end(s) diameter 1.378", threaded bolt M2	Rod combination	2-piece folding design
	Special features	for precise and vertical fit
Type bla	Tube end(s)	diameter 1.378", threaded bolt M20
.,,,,,	Туре	black

Steel rod combination for use in subwoofers with M20 connection. The height is fixed with a safety hook and secured with a low-noise, backlash-free clamping screw. The slim design of the clamp enables space-saving transportation and ensures a stylish appearance. The usable height is between 33.425 and 54.212" and is achieved in 4 steps of 5.196". A plastic cap protects the speaker from scratching.



Telefax: +49 (0) 9342-806-150

E-Mail: contact(at)k-m.de