

24730

Wind-up stand »3000«

Product variant

US-24730-000-55 - black

Data

Base diameter	61.024 "
EAN	4016842117062
Height	from 55.315 to 118.11"
Height adjustment	hand crank with push-button system and locking screw
Leg construction	tube legs with double cross braces
Material	aluminum
Max. load capacity*	88.106 lbs
Number of legs	3
Product Category	Starline
Rod combination	3-piece folding design
Size when folded	54.724 x 7.874 x 6.496"
Special features	steel extension tubes; push-button system and hand crank avoid uncontrolled reverse motion; locking screw provides additional safety; zinc die-cast connecting parts
Tube end(s)	diameter 1.378", integrated threaded bush M10 for crossbars
Type	black
Weight	26.432 lbs



Professional patented light and speaker stand with an innovative dual crank mechanism. A low base height of 55.315" ensures easy, ergonomic positioning of the load. The 3-piece tube combination reaches a height of 118.11". Lifting and lowering the load is user-friendly, safe and reliable via two separate crank gears. The integrated »AutoLock« system prevents sudden lowering of the load by automatic locking. The crank can also be removed to prevent unauthorised use. Since no cables are needed, the stand is completely maintenance-free. The robust stand focuses on stability and steadiness, so that the 5° stability test according to DIN 56950-3 with a load capacity of 88.106 lbs is easily realised. The compact transport dimensions are 54.724 x 7.874 x 6.496" and the weight is approx. 26.432 lbs. The integrated M10 threaded bush allows additional trusses or individual spotlights to be mounted directly.