

24654

## Lighting/Speaker stand »Pro«

### Product variant

US-24654-000-55 - black

### Data

|                     |  |
|---------------------|--|
| Base dimensions     | 21.65 x 21.65"   |
| EAN                 | 4016842122721  |
| Gewicht             | 38.36 lbs  |
| Height              | from 55.91 to 95.28"   |
| Height adjustment   | spring-loaded bolt and locking screw   |
| Leg construction    | flat steel plate   |
| Material            | steel  |
| Max. load capacity* | 66.139 lbs   |
| Quality level       | Starline   |
| Rod combination     | 2-piece folding design   |
| Special features    | integrated shock absorber;<br>gradual height adjustment system:<br>depending on the requirements, there are<br>three ways to position the distance rod |
| Tube end(s)         | diameter 1.378", integrated threaded bush<br>M10 for crossbars   |
| Type                | black  |



Attractive stand for lights and loudspeaker cabinets. Thanks to the heavy, flat steel plate (21.653 x 21.653"), the stand is ideal for use where space is at a premium. Depending on requirements, there are three ways to position the pole. In addition to the centric and off-center position, the tube combination can also be mounted in the corner. A carrying handle, a cable management system and four stable feet are further useful features. The usable height is between 55.905 and 95.275" and can be reached in 5 steps of 7.874". The tried and tested K&M clamping screw and the robust locking bolt are used for fixing. The integrated M10 threaded bush enables the attachment of a truss or the direct attachment of lights. The maximum centric load capacity with full extension is 66.138 lbs.