

**Product variant** 

US-24654-000-55 - black

## 24654 Lighting/Speaker stand »Pro«

US-24054-000-55 - Diack	
Data	
Base dimensions	21.65 x 21.65"
EAN	4016842122721
Gewicht	38.36 lbs
Height	from 55.91 to 95.28"
Height adjustment	spring-loaded bolt and locking screw
Leg construction	flat steel plate
Material	steel
Max. load capacity*	66.139 lbs
Quality level	Starline
Rod combination	2-piece folding design
Special features	integrated shock absorber; gradual height adjustment system: depending on the requirements, there are three ways to position the distance rod
Tube end(s)	diameter 1.378", integrated threaded bush M10 for crossbars
Туре	black



Attractive stand for lights and loudspeaker cabinets. Thanks to the heavy, flat steel plate (21.653 x 21.653"), the stand is ideal for use where space is at a premium. Depending on requirements, there are three ways to position the pole. In addition to the centric and off-center position, the tube combination can also be mounted in the corner. A carrying handle, a cable management system and four stable feet are further useful features. The usable height is between 55.905 and 95.275" and can be reached in 5 steps of 7.874". The tried and tested K&M clamping screw and the robust locking bolt are used for fixing. The integrated M10 threaded bush enables the attachment of a truss or the direct attachment of lights. The maximum centric load capacity with full extension is 66.138 lbs.

Kiesweg 2, 97877 Wertheim/Main Phone: +49 (0) 9342-806-0 Telefax: +49 (0) 9342-806-150 E-Mail: contact(at)k-m.de

